

AMATEI'S CONCRETE NAILS




Wire Connected Round Nails for nail guns

Advantages

HARD TO BE BROKEN !

KOBERCO's high quality steel wire rod and special quenching technology used.

Amatei's hardness standard keeps HRC 51-57.



«90 degrees bending test results»

Amatei product

made in other country




No breakage against 90 degrees




Broken less than 90 degrees

Uses


driving a nail into a board



Drive a nail into a board in advance.




Position it on the concrete.




Drive it into the wall.


materials available



concrete




bricks



steel sheets



mortar blocks



building blocks

Concrete Nails Size Range

product No.	size(mm)			quantity per 500g (aprx.)	weight/carton (kg)	shank shape	
	length	shank diameter	head diameter			smooth type	with groove
#12 × 25	25	2.77	5.4	390 pcs	10	available	
#12 × 32	32	2.77	5.4	300 pcs	10	available	
#12 × 38	38	2.77	5.4	260 pcs	10	available	available
#12 × 50	50	2.77	5.4	200 pcs	10	available	available
#10 × 65	65	3.40	6.5	94 pcs	10		available
#10 × 75	75	3.40	6.5	82 pcs	10		available
#9 × 25	25	3.76	7.0	190 pcs	10		available
#9 × 38	38	3.76	7.0	130 pcs	10		available
#9 × 50	50	3.76	7.0	100 pcs	10		available
#8 × 65	65	4.19	7.7	60 pcs	10		available
#7 × 75	75	4.57	9.0	45 pcs	10		available
#7 × 90	90	4.57	9.0	40 pcs	10		available
#7 × 100	100	4.57	9.0	35 pcs	10		available

Wire Connected Round Nails Size Range

quantity: 300 pcs/1 roll, 10 rolls/carton

product No.	head diameter	diameter	length	weight/carton
NC2532K	5.6mm	2.5mm	32mm	7.7kg
NC2538K	5.6mm	2.5mm	38mm	9.3kg
NC2542K	5.6mm	2.5mm	42mm	10.3kg
NC2545K	5.6mm	2.5mm	45mm	10.8kg
NC2550K	5.6mm	2.5mm	50mm	12.1kg
NC2557K	5.6mm	2.5mm	57mm	13.7kg
NC2565K	5.6mm	2.5mm	65mm	15.4kg

Shimizu Co.,Ltd.

website: www.shimizu-net.co.jp

email: info@shimizu-net.co.jp